

IB INTERNATIONAL

DEWATERING & IRRIGATION

QUICK CONNECT COUPLINGS



A-TYPE
B-TYPE
C-TYPE
F-TYPE

SIZES 2" to 16"
Largest Range



IB International Pty Ltd

Ph: 07 3348 8300 | Fax: 07 3348 8900 | www.ibinternational.com.au

Technical Specifications

A-TYPE

Female Part with 2 Hooks

Diameter	Working Pressure	Maximum Deviation of Cone
60mm	19 bars	
80mm	16 bars	
100mm	14 bars	
120mm	13 bars	
150mm	15 bars	28°
200mm	8 bars	14°
250mm	5 bars	16°
300mm	4 bars	16°

F-TYPE

Female Part with 2 Hooks

Diameter	Working Pressure	Maximum Deviation of Cone
50mm	15 bars	26°
60mm	10 bars	28°
80mm	9 bars	30°
100mm	8 bars	28°
120mm	7 bars	26°
150mm	6 bars	22°

A-TYPE

Female Part with 3 Hooks

Diameter	Working Pressure	Maximum Deviation of Cone
100mm	19 bars	
120mm	17 bars	
150mm	20 bars	28°
200mm	10 bars	14°
250mm	6 bars	16°
300mm	5 bars	16°

F-TYPE

Female Part with 3 Hooks

Diameter	Working Pressure	Maximum Deviation of Cone
60mm	15 bars	28°
80mm	12 bars	30°
100mm	11 bars	28°
120mm	10 bars	26°
150mm	9 bars	22°

B-TYPE

Interchangeable with existing Bauer type

Diameter	Working Pressure	Maximum Deviation of Cone
2"	20 bars	30°
3"	20 bars	30°
3 1/2"	20 bars	30°
4"	12 bars	30°
5"	12 bars	20°
6"	12 bars	20°
8"	12 bars	20°
10"	12 bars	16°
12"	12 bars	16°

