

IB INTERNATIONAL

MINING

EVAPORATION WASHDOWN DUST CONTROL

Climber Cannon (16°- 46°) Specs

Base Size: 63 BSPF
Primary Nozzle Size: 26 - 34mm
Radius: 42 - 67 metres
Flow LPM: 800 - 2162

Kronos Cannon (16°- 46°) Specs

Base Size: Flanged
Primary Nozzle Size: 22 - 40mm
Radius: 40 - 78 metres
Flow LPM: 522 - 2834



INTRODUCING:

CLIMBER
GEAR DRIVE WATER CANON

KRONOS
IMPACT WATER CANON

IB
INTERNATIONAL

IB International Pty Ltd

Ph: 07 3399 1288 | Fax: 07 3902 0088 | www.ibinternational.com.au

IB INTERNATIONAL

**NEW
WAY**

Skipper Washdown Canon Specs

Base Size: 40 BSPF

Primary Nozzle Size: 12-20mm Standard 16mm

Nozzle Radius: 22-41mm

Flow LPM: 159-617

Stainless Steel Washdown Nozzle: 15 & 30deg



**OLD
WAY**



IB
INTERNATIONAL

IB International Pty Ltd
07 3399 1288 | Fax: 07 3902 0088 | www.ibinternational.com.au