

IB International Pty Ltd OCMIS HARD HOSE PERFORMANCE CHART

MAY 2005

MODEL : 110 / 250 mt. HOSE WALL 8mm

NOZ SIZE	NOZ RADIUS	GUN WIDTH	WETTED WIDTH x 80%	CAPACITY			AREA PER RUN Ha.	mm = Application rate per irrigated run																	
				Lt/Sec	Lt/Min	M3/h		10 mm	15 mm	20 mm	25 mm	30 mm	35 mm	40 mm	50 mm	60 mm									
								Travel speed & pressure required at the machine																	
								mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar		
28	3.0	44	70	14.13	848	50.88	2.00	72	5.0	48	4.8	36	4.7	29	4.6	24	4.5	21	4.4	18	4.4	14	4.3	12	4.3
	4.0	48	77	16.35	981	58.86	2.21	77	6.3	51	6.1	38	6.0	31	5.9	26	5.8	22	5.7	19	5.7	15	5.6	13	5.6
	4.5	50	80	17.33	1040	62.40	2.32	78	6.9	52	6.7	39	6.6	31	6.5	26	6.4	22	6.3	20	6.3	16	6.3	13	6.2
	5.0	52	83	18.27	1096	65.76	2.43	79	7.6	53	7.4	40	7.3	32	7.2	26	7.1	23	7.0	20	7.0	16	6.9	13	6.9
	5.5	54	86	19.15	1149	68.94	2.54	80	8.2	53	8.0	40	7.9	32	7.8	27	7.7	23	7.6	20	7.6	16	7.5	13	7.5
	6.0	55	88	20.03	1202	72.12	2.60	82	8.8	55	8.6	41	8.5	33	8.4	27	8.3	23	8.2	20	8.2	16	8.2	14	8.1
RECOMMENDED GEAR SELECTION								2.2		2.2		3.1		3.1		1.2		2.1		2.1		2.1		1.1	
30	3.0	46	74	16.23	974	58.44	2.10	79	5.3	53	5.1	40	5.0	32	4.9	26	4.8	23	4.7	20	4.7	16	4.6	13	4.6
	4.0	50	80	18.78	1127	67.62	2.32	85	6.6	56	6.4	42	6.3	34	6.2	28	6.1	24	6.0	21	6.0	17	6.0	14	5.9
	4.5	52	83	19.92	1195	71.70	2.43	86	7.3	57	7.1	43	7.0	34	6.9	29	6.8	25	6.7	22	6.7	17	6.7	14	6.6
	5.0	54	86	21.00	1260	75.60	2.54	88	8.0	58	7.8	44	7.7	35	7.6	29	7.5	25	7.4	22	7.4	18	7.3	15	7.3
	5.5	55	88	22.00	1320	79.20	2.60	90	8.7	60	8.5	45	8.4	36	8.3	30	8.2	26	8.1	23	8.1	18	8.0	15	8.0
RECOMMENDED GEAR SELECTION								3.2		2.2		3.1		3.1		1.2		2.1		2.1		2.1		1.1	
32	4.0	52	83	21.37	1282	76.92	2.43	92	7.0	62	6.8	46	6.7	37	6.6	31	6.5	26	6.4	23	6.4	18	6.4	15	6.3
	4.5	53	85	22.65	1359	81.54	2.48	96	7.8	64	7.6	48	7.5	38	7.4	32	7.3	27	7.2	24	7.2	19	7.1	16	7.1
	5.0	56	90	23.88	1433	85.98	2.65	96	8.5	64	8.3	48	8.2	38	8.1	32	8.0	27	7.9	24	7.9	19	7.8	16	7.8
	5.5	57	91	25.02	1501	90.06	2.71	99	9.2	66	9.0	49	8.9	40	8.8	33	8.7	28	8.6	25	8.6	20	8.6	16	8.5
	6.0	59	94	26.17	1570	94.20	2.82	100	9.9	67	9.7	50	9.6	40	9.5	33	9.4	29	9.3	25	9.3	20	9.3	17	9.2
RECOMMENDED GEAR SELECTION								3.2		2.2		3.1		3.1		3.1		3.1		2.1		2.1		1.1	

N.B. This is page 2 of 2 Page 1 = nozzle sizes 22, 24, 26mm
Page 2 = nozzle sizes 28, 30, 32mm

N.B. These tables are merely indicative because they have been worked out through a mathematical formula and according to average working conditions . Consequently Ocmis and IB International decline any responsibilities deriving from their application .