

IB International Pty Ltd OCMIS HARD HOSE PERFORMANCE CHART

MAY 2005

MODEL : 125 / 550 mt. HOSE WALL 11.4 mm

NOZ SIZE	NOZ RADIUS	GUN WIDTH	WETTED x 80%	CAPACITY			AREA PER RUN	mm = Application rate per irrigated run																			
				Lt/Sec	L/Min	M3/h		10 mm		15 mm		20 mm		25 mm		30 mm		35 mm		40 mm		50 mm		60 mm			
RECOMMENDED GEAR SELECTION				Travel speed & pressure required at the machine																							
mm	bar	mt					Ha.	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar		
26	3.0	41	66	12.20	732	43.92	3.81	67	5.1	45	4.9	33	4.9	27	4.8	22	4.7	19	4.7	17	4.7	13	4.6	11	4.6		
	4.0	46	74	14.10	846	50.76	4.31	69	6.5	46	6.3	34	6.3	28	6.2	23	6.1	20	6.1	17	6.1	14	6.0	11	6.0		
	4.5	48	77	14.97	898	53.88	4.52	70	7.1	47	6.9	35	6.9	28	6.8	23	6.7	20	6.7	18	6.7	14	6.6	12	6.6		
	5.0	51	82	15.77	946	56.76	4.82	70	7.8	46	7.6	35	7.6	28	7.5	23	7.4	20	7.4	17	7.4	14	7.3	12	7.3		
	5.5	52	83	16.52	991	59.46	4.93	71	8.4	48	8.2	36	8.2	29	8.1	24	8.0	20	8.0	18	8.0	14	7.9	12	7.9		
RECOMMENDED GEAR SELECTION								2. 2		3. 1		1. 2		1. 2		2. 1		2. 1		2. 1		1. 1		1. 1			
28	3.0	44	70	14.13	848	50.88	4.11	72	5.5	48	5.3	36	5.3	29	5.2	24	5.1	21	5.1	18	5.1	14	5.0	12	5.0		
	4.0	48	77	16.35	981	58.86	4.52	77	6.9	51	6.7	38	6.7	31	6.6	26	6.5	22	6.5	19	6.5	15	6.4	13	6.4		
	4.5	50	80	17.33	1040	62.40	4.72	78	7.6	52	7.4	39	7.4	31	7.3	26	7.2	22	7.2	20	7.2	16	7.1	13	7.1		
	5.0	52	83	18.27	1096	65.76	4.93	79	8.3	53	8.1	40	8.1	32	8.0	26	7.9	23	7.9	20	7.9	16	7.8	13	7.8		
	5.5	54	86	19.15	1149	68.94	5.13	80	9.0	53	8.8	40	8.8	32	8.7	27	8.6	23	8.6	20	8.6	16	8.5	13	8.5		
	6.0	55	88	20.03	1202	72.12	5.24	82	9.7	55	9.5	41	9.5	33	9.4	27	9.3	23	9.3	20	9.3	16	9.2	14	9.2		
RECOMMENDED GEAR SELECTION								2. 2		3. 1		3. 1		1. 2		1. 2		2. 1		2. 1		1. 1		1. 1			
30	3.0	48	77	16.23	974	58.44	4.52	76	5.9	51	5.7	38	5.7	30	5.6	25	5.5	22	5.5	19	5.5	15	5.4	13	5.4		
	4.0	52	83	18.78	1127	67.62	4.93	81	7.4	54	7.2	41	7.2	33	7.1	27	7.0	23	7.0	20	7.0	16	6.9	14	6.9		
	4.5	53	85	19.92	1195	71.70	5.03	85	8.2	56	8.0	42	8.0	34	7.9	28	7.8	24	7.8	21	7.8	17	7.7	14	7.7		
	5.0	56	90	21.00	1260	75.60	5.34	84	8.9	56	8.7	42	8.7	34	8.6	28	8.5	24	8.5	21	8.5	17	8.4	14	8.4		
	5.5	58	93	22.00	1320	79.20	5.55	85	9.7	57	9.5	43	9.5	34	9.4	28	9.3	24	9.3	21	9.3	17	9.2	14	9.2		
	6.0	60	96	23.02	1381	82.86	5.76	86	10.5	58	10.3	43	10.3	35	10.2	29	10.1	25	10.1	22	10.1	17	10.0	14	10.0		
RECOMMENDED GEAR SELECTION								2. 2		2. 2		3. 1		1. 2		1. 2		1. 2		2. 1		2. 1		1. 1			
32	4.0	54	86	21.37	1282	76.92	5.13	89	8.0	59	7.8	45	7.8	36	7.7	30	7.6	25	7.6	22	7.6	18	7.5	15	7.5		
	4.5	56	90	22.65	1359	81.54	5.34	91	8.9	61	8.7	46	8.7	36	8.6	30	8.5	26	8.5	23	8.5	18	8.4	15	8.4		
	5.0	58	93	23.88	1433	85.98	5.55	93	9.7	62	9.5	46	9.5	37	9.4	31	9.3	26	9.3	23	9.3	19	9.2	15	9.2		
	5.5	60	96	25.02	1501	90.06	5.76	94	10.5	63	10.3	47	10.3	38	10.2	31	10.1	27	10.1	23	10.1	19	10.0	16	10.0		
	6.0	62	99	26.17	1570	94.20	5.97	95	11.3	63	11.1	47	11.1	38	11.0	32	10.9	27	10.9	24	10.9	19	10.8	16	10.8		
RECOMMENDED GEAR SELECTION								3. 2		2. 2		3. 1		1. 2		1. 2		1. 2		2. 1		2. 1		1. 1			
34	4.5	57	91	25.60	1536	92.15	5.44	101	9.7	67	9.5	51	9.5	40	9.4	34	9.3	29	9.3	25	9.3	20	9.2	17	9.2		
	5.0	59	94	26.98	1619	97.14	5.65	103	10.6	69	10.4	51	10.4	41	10.3	34	10.2	29	10.2	26	10.2	21	10.1	17	10.1		
	5.5	61	98	28.27	1696	101.76	5.87	104	11.4	70	11.2	52	11.2	42	11.1	35	11.0	30	11.0	26	11.0	21	10.9	17	10.9		
RECOMMENDED GEAR SELECTION								3. 2		2. 2		3. 1		3. 1		1. 2		1. 2		1. 2		1. 2		1. 1			
36	4.5	58	93	28.68	1721	103.26	5.55	111	10.6	74	10.4	56	10.4	45	10.3	37	10.2	32	10.2	28	10.2	22	10.1	19	10.1		
	5.0	61	98	30.23	1814	108.84	5.87	112	11.6	74	11.4	56	11.4	45	11.3	37	11.2	32	11.2	28	11.2	22	11.1	19	11.1		
RECOMMENDED GEAR SELECTION								3. 2		2. 2		3. 1		3. 1		1. 2		1. 2		2. 1		2. 1		2. 1			

N.B. These tables are merely indicative because they have been worked out through a mathematical formula and according to average

working conditions . Consequently Ocmis and IB International decline any responsibilities deriving from their application .