

IB International Pty Ltd OCMIS HARD HOSE PERFORMANCE CHART

MAY 2005

MODEL : 70 / 350 mt. HOSE WALL 5.2mm

NOZ	NOZ	GUN	WETTED	CAPACITY			AREA	mm = Application rate per irrigated run																
				Lt/Sec	Lt/Min	M3/h		PER	10 mm	15 mm	20 mm	25 mm	30 mm	35 mm	40 mm	50 mm	60 mm							
SIZE	RADIUS	WIDTH					RUN	Travel speed & pressure required at the machine																
mm	bar	mt	x 80%				Ha.	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	mth	bar	
14	2.0	25	40	2.90	174	10.44	1.46	26	3.8	17	3.4	13	3.4	10	3.3	9	3.3	7	3.3					
	3.0	29	46	3.53	212	12.72	1.71	27	5.1	18	4.7	14	4.7	11	4.6	9	4.6	8	4.6					
	3.5	30	48	3.82	229	13.74	1.78	29	5.7	19	5.3	14	5.3	11	5.2	10	5.2	8	5.2					
	4.0	32	51	4.08	245	14.70	1.90	29	6.4	19	6.0	14	6.0	11	5.9	10	5.9	8	5.9					
	4.5	33	53	4.33	260	15.60	1.97	30	7.0	20	6.6	15	6.6	12	6.5	10	6.5	8	6.5					
	5.5	35	56	4.78	287	17.22	2.10	31	8.3	21	7.9	15	7.9	12	7.8	10	7.8	9	7.8	8	7.7			
RECOMMENDED GEAR SELECTION								3		2		1		1		1		1		1				
16	3.0	32	51	4.60	276	16.56	1.90	32	5.7	22	5.3	16	5.3	13	5.2	11	5.2	9	5.2	8	5.1			
	4.0	36	58	5.33	320	19.20	2.17	33	7.2	22	6.8	17	6.8	13	6.7	11	6.7	10	6.7	8	6.6			
	4.5	37	59	5.63	338	20.28	2.23	34	7.9	23	7.5	17	7.5	14	7.4	11	7.4	10	7.4	9	7.3			
	5.0	39	62	5.93	356	21.36	2.36	34	8.7	23	8.3	17	8.3	14	8.2	11	8.2	10	8.2	9	8.1			
	5.5	41	66	6.22	373	22.38	2.50	34	9.4	23	9.0	17	9.0	14	8.9	11	8.9	10	8.9	9	8.8			
RECOMMENDED GEAR SELECTION								3		2		2		1		1		1		1				
18	3.0	33	53	5.83	350	21.00	1.97	40	6.6	27	6.2	20	6.2	16	6.1	13	6.1	11	6.1	10	6.0	8	6.0	
	4.0	37	59	6.73	404	24.24	2.23	41	8.3	27	7.9	20	7.9	16	7.8	14	7.8	12	7.8	10	7.7	8	7.7	
	4.5	39	62	7.15	429	25.74	2.36	41	9.2	28	8.8	21	8.8	17	8.7	14	8.7	12	8.7	10	8.6	8	8.6	
	5.0	41	66	7.53	452	27.12	2.50	41	10.0	28	9.6	21	9.6	17	9.5	14	9.5	12	9.5	10	9.4	8	9.4	
	5.5	42	67	7.90	474	28.44	2.57	42	10.9	28	10.5	21	10.5	17	10.4	14	10.4	12	10.4	11	10.3	8	10.3	
RECOMMENDED GEAR SELECTION								3		2		2		1		1		1		1		1		
20	3.0	35	56	7.20	432	25.92	2.10	46	7.7	31	7.3	23	7.3	19	7.2	15	7.2	13	7.2	12	7.1	9	7.1	
	4.0	39	62	8.35	501	30.06	2.36	48	9.8	32	9.4	24	9.4	19	9.3	16	9.3	14	9.3	12	9.2	10	9.2	
	4.5	41	66	8.85	531	31.86	2.50	49	10.8	32	10.4	24	10.4	19	10.3	16	10.3	14	10.3	12	10.2	10	10.2	
RECOMMENDED GEAR SELECTION								3		3		2		2		2		1		1		1		1

N.B. These tables are merely indicative because they have been worked out through a mathematical formula and according to average working conditions . Consequently Ocmis and IB International decline any responsibilities deriving from their application .